



## CLASSIC LINE

[EXC]

**The ultimate choice in comfort and protection! EXC is designed for prolonged use in tough environments.**

Unique, moulded polyurethane inserts provides maximum space for the ear and gives great comfort. The EXC can be equipped with a variety of visors and is suitable for most noise situations.

- Available both as headband and helmet attachment.
- Wide and padded headband gives a secure and comfortable fit.
- Adjustable headband pressure.
- Sure-grip headband makes it easy to put on and take off muffs, even if you wear gloves.
- Helmet attachment, with a patented spring design, offers low pressure tension and a high level of comfort.
- The helmet attachment has three distinct positions for easy handling.
- Unique, moulded polyurethane inserts provides maximum space for the ear and great comfort during prolonged use.
- Weight: 232 g (Headband) 218 g (Helmet mounted)





### EXC Headband #20010

EN352-1:1993 : SNR = 27 dB, H=31 dB, M=24 dB, L=16 dB

Frequency [Hz]	63	125	250	500	1000	2000	4000	8000
Mean value [dB]	13,7	11,2	19,1	25,7	29,2	32,0	36,8	39,0
Std.dev. [dB]	3,9	3,2	2,2	2,7	3,1	2,3	2,7	3,7
APV value [dB]	9,8	8,0	16,9	23,0	26,1	29,7	34,1	35,3

ANSI S3.19-1974: NRR = 24

### EXC Helmet mounted #10010

EN352-3:1996 : SNR = 26 dB, H=29 dB, M=23 dB, L=15 dB

Frequency [Hz]	63	125	250	500	1000	2000	4000	8000
Mean value [dB]	11,4	11,1	18,1	25,1	27,0	28,6	38,6	40,2
Std.dev. [dB]	3,7	3,3	3,3	3,1	2,3	2,4	2,6	3,3
APV value [dB]	7,7	7,8	14,8	22,0	24,7	26,2	36,0	36,9

ANSI S3.19-1974: NRR = 25